

Cream Wax

TECHNICAL DATA CREAM WAX

Issued on 21/11/2024 - Rev. n. 1 of 21/11/2024

Description:

Cream Wax is a ready-to-use, water-based paraffin wax specifically designed for protecting interior walls treated with Marmorino Lime, Cemento 3D, Marbled Mirror, and ArchiMetal. Cream Wax creates a velvety, easy-to-clean, environmentally sustainable, and advanced layer. It contains no added *formaldehyde or **APEO, and has a very low VOC content.

Use:

- Cream Wax protects and decorates interior walls of shops, warehouses, hospitals, bars, restaurants, mechanical, pharmaceutical, and food industries, private homes, hotels, etc.

Preparation and application of Cream Wax:

- The product is ready to use; stir before use.
1. Apply a first coat of Cream Wax using a stainless-steel trowel over the entire surface.
 2. Let dry for 6 hours (+20°C).
 3. Apply a second coat of Cream Wax, using the same method as the first coat.
 4. Let dry for 12 hours (+20°C);
 5. Polish the entire Cream Wax-treated surface using an electric polisher with the appropriate soft wool pad.

Cream Wax Technical Data:

- Appearance: Creamy;
- Composition: Blend of paraffin waxes in aqueous dispersion;
- Yield: 63 g/m² in two coats depending on the surface's absorbency;
- Color: Characteristic;
- Specific weight: 0.850 kg/l +/- 3%;
- Viscosity: ≈8,000 mPas;
- pH: >9;
- Application temperature: +5°C ÷ +30°C;
- Curing time before cleaning: 7 days;
- Cleaning recommendations: A damp microfiber cloth;
- Tool cleaning: Water;
- Packaging: 2.5 L and 1 L;
- Storage: 24 months in a cool place, away from heat sources. (+10°C and +35°C).

*Since January 1, 2016, formaldehyde has been classified as a carcinogen in Italy. The IARC (International Agency for Research on Cancer) classifies these substances based on their harmfulness to humans. **APEO-free indicates a product free of APEO (alkylphenol ethoxylate), a substance hazardous to the environment and aquatic organisms. The REACH regulation (Regulations EC 552/2009 EC 1907/2006 REACH) prohibits the use of APEO in concentrations equal to or greater than 1,000 ppm (parts per million) in Europe.

The written and verbal technical and application instructions provided to buyers and installers are based on our experience and the current state of the art in theory and practice. They are not binding and do not imply any contractual obligation or secondary commitment arising from the purchase contract. They do not exempt the buyer from personally verifying the suitability of our products for the intended application, at their own risk. The processing cycles indicated above do not constitute any assumption of liability by Nikkolor Italia s.r.l., which is exempt from any liability for problems arising from incorrect installation.

Nikkolor Italia s.r.l.

V.le Vittorio Veneto, 186 - 96014 Floridia (SR)
+39 0931 941789 - www.nikkolor.net