

Decor Finish

TECHNICAL DATA DECOR FINISH

Issued on 15/09/2015 - Rev. n. 1 of 05.09.2023

Description:

Latest-generation, single-component, water-based, nanostructured polyacrylic clear coat. Non-slip, waterproof, and drive-over. Protects and decorates both interior and exterior floors and walls.

Intended use:

- Decor Finish is designed for the protection and decoration of floors and walls in Cemento 3D, MarmUra, Etna, Terra Veneziana, and/or Microcem-FB.
- Its use varies among shops, warehouses, hospitals, bars, restaurants, mechanical, pharmaceutical, and food industries, private homes, poolsides, shower stalls, kitchen countertops, furniture accessories, etc.

Substrate preparation:

- Floors or shower stalls coated in Cemento 3D, MarmUra, Etna, Terra Veneziana, and/or Microcem-FB must be dry and cured, clean, and free of cracks, release agents, dust, and anything else that could compromise perfect adhesion.

Product Preparation:

- Decor Finish is ready to use; mix thoroughly before application.

Product Application:

- Decor Finish is applied in two or three coats using a short-haired roller;
- Applying Decor Finish Matte directly to white or pastel-colored surfaces is not recommended; the matting agent it contains may alter the final appearance of the surface. We recommend applying a first coat of Decor Finish Semi-gloss and then proceeding with the matte finish.

Information:

- Do not apply the product if there is any counter-pressure moisture;
- Durability depends primarily on the thickness applied and the type and intensity of wear to the surface;
- To maintain its attractive appearance, we recommend regular cleaning and care of the surface;
- Clean packaging is 100% recyclable;
- For information on proper disposal, storage, and handling of the product, please consult the relevant Safety Data Sheet.
- Drying time before walking on it is 36 hours;
- Use water and install furniture 10 days after applying the final coat;
- The application time may be longer depending on ambient humidity and the season; on average, seven days are required at 30°C, ten days at 20°C, and 15 days at 10°C;
- Apply the product at least 4°C above the dew point;
- Do not cover the surface during the seven-day drying period;
- Do not place sheets or cardboard, furniture, sofas, tables, or chairs on top of it while it dries; encourage ventilation;
- When applying outdoors, consider the optimal slope of the treated surface to allow water to drain away and avoid long-term waterlogging;
- Decor Finish decorates and protects seamless surfaces but does not make them indestructible.

Features:

- Excellent surface finish
- Waterproof and dustproof
- Easily washable
- Abrasion-resistant
- Drive-over surface
- Resistant to moderate forklift traffic
- Consolidating effect
- Free from organic solvents
- Can be applied indoors, odorless
- Versatile product, adheres to any surface
- Resists temperature changes
- Requires minimal maintenance even after years of use

Nikkolor Italia s.r.l.

V.le Vittorio Veneto, 186 - 96014 Floridia (SR)
+39 0931 941789 - www.nikkolor.net

Decor Finish

- Easy application
- The product is formulated with a low environmental impact.

Technical data:

- Practical coverage: 8-10 m²/l, variable depending on the roughness and absorption of the substrate;
- Specific weight: 1.0 ± 0.05 at 20°C;
- Color: Milky for the semi-gloss version, straw-yellow for the matte version;
- Resistance to operating temperatures: up to 70°C;
- Store in tightly closed original containers in a dry place between +5°C and +30°C;
- Slip resistance: DIN 51097 Class A method 12° ≤ α < 18° - Non-slip (DIN 51130): R11 (Decor Finish AS);
- Packaging: 2.5 L;
- Safety (per EEC regulation): The product is not flammable or dangerous;
- Symbols: Not subject to labeling, the product does not require labeling pursuant to Legislative Decree no. No. 65 of 14/03/2003 and subsequent amendments and updates;
- VOC classification: (Legislative Decree 27 March 2006 No. 161): High-performance single-component paints;
- EU VOC limit value for DECOR FINISH AS (cat. I/BA): 140 g/L. DECOR FINISH AS contains a maximum of 140 g/L of VOCs;
- Safety (Criteria EC Regulation 1272/2008 (CLP)): The product is not considered hazardous. Precautionary statements: Not subject;
- Risk phrases: Not subject;
- Symbols: Not subject;
- Land transport ADR/RID: Not subject;
- The product is not considered hazardous according to EC Regulation 1272/2008 (CLP). Special provisions: EUH 210. Safety data sheet available upon request.

Pursuant to Legislative Decree No. 161/06, the VOC values shown on the packaging refer to the specified dilutions and thinners and to products tinted according to the formulations indicated by Nikkolor Italia.

The written and verbal technical and application instructions provided to purchasers and installers are based on our experience and the current state of the art, both theoretically and practically. They are not binding and do not imply any contractual obligation or secondary commitment arising from the purchase contract. They do not exempt the purchaser from personally verifying, at their own responsibility, the suitability of our products for the intended application. The processing cycles indicated above do not constitute any assumption of liability by Nikkolor Italia s.r.l., which is exempt from any liability for problems arising from incorrect installation.

Nikkolor Italia s.r.l.

V.le Vittorio Veneto, 186 - 96014 Floridia (SR)
+39 0931 941789 - www.nikkolor.net