

Only Cement

ROCK CEMENT

APPLICATION METHOD

SUBSTRATES:

- Substrates must be dry, solid, and free of dust, paint, wax, oil, loose particles, and seasoned surfaces.

APPLICATION:

- The recommended mix is 1 liter of drinking water for every 2 kg of Cemento 3D.
 1. Wearing latex gloves, apply the product to the entire surface using your hands to create a rough outline for subsequent steps.
 2. Let dry for 24 hours (+20°C).
- The recommended mix is 1 liter of drinking water for every 4 kg of Cemento 3D.
 1. Wearing latex gloves, apply the product to the entire surface using your hands and shape the desired texture (spatulas or trowels can be used to create edges and straight, transverse, and diagonal lines).
 2. Lightly spray water onto the surface using a hand sprayer and, using a damp sponge, shape the desired rock shape.
 3. Let dry for 24 hours (+20°C).
- The recommended dosage is 1 liter of drinking water for every 2 kg of Cemento 3D.
 1. Apply the product using a brush to the entire surface or just to the desired areas.
 2. Dab the product before it dries using a damp sponge.
 3. Let it dry for 24 hours (+20°C).

COLORING:

1. Using a brush, apply the first coat of Velatura Silossanica diluted 50% with drinking water.
2. Let it dry for 24 hours (+20°C).
3. Using a sponge and/or brush, apply a second coat of Velatura Silossanica in the desired color.