



Daranà Gold

Liquid Metal

Luxury that shines.
The matter that enchants.

SIAE DALLA
PARTE
DI CHI
CREA



DARANÀ®

DECORATIVE SYSTEM WITH LIQUID METAL EFFECT

**IT IS NOT A PAINT.
IT IS AN EVOLUTION OF MATERIAL.**

Daranà is an innovative system that reproduces real liquid metal in solid form. Highly three-dimensional surfaces capture light and transform any environment into a work of design.



INOX



GOLD

- REAL METAL EFFECT**
Authentic reflections and dynamic
- HIGHLY THREE-DIMENSIONAL SURFACES**
Unique depth and materiality
- APPLICATION WITH FOIL**
Exclusive Daranà system
- FOR WALLS, SOFT FURNISHINGS AND FURNITURE**
Maximum versatility of use
- HIGH AESTHETIC IMPACT**
Perfect for design environments



1 OPEN SPACE – INOX
Contemporary design with refined metallic reflections.
Surfaces that enhance light and space.



2 BEDROOM – GOLD
Warm and sophisticated atmosphere.
Metal becomes emotion.



3 KITCHEN – INOX
Durability and design for modern environments.
The perfect balance between aesthetics and function.



4 DETAILS – GOLD
Real three-dimensionality that enhances every surface.
Every wall becomes the protagonist.

REAL METAL EFFECT
Authentic reflections and sophistication

HIGHLY THREE-DIMENSIONAL SURFACES
Depth, light and movement

APPLICATION WITH FOIL
Innovative system exclusive to Daranà

FOR INTERIORS
Suitable for walls, soft furnishings, furniture and accessories

HIGH AESTHETIC IMPACT
Ideal for design and luxury environments

INNOVATIVE AND REFINED
Combines science, materials and innovation

TECHNICAL DATA

- Coverage: approx. 14 m²
- Daranà Measure: 21 x 64 ml
- Available Colors: Inox / Gold
- System: Daranà Foil + Decor Fix
- Application: Indoor



DARANÀ

DESCRIPTION

Daranà© is NOT a paint, and as such, it doesn't come in the traditional jar packaging typical of decorative products. It's a true innovation in decoration, allowing you to reproduce a metallic effect in liquid form. Its innovative structure allows you to decorate any surface: walls, ceilings, furniture, and furnishings can be enhanced with a simple gesture! DARANÀ© is the combination of science and innovation.

FIELDS OF USE

- ✓ Ideal for covering interior walls and ceilings intended for high-end design and for the renovation of public and private spaces, shopping centers, shops, bars, villas, and residences.
- ✓ A true innovation in modern architecture, a refined finish capable of creating three-dimensionality on the surfaces it covers, a timeless effect that adds a minimalist touch to your spaces.

SUBSTRATES

- ✓ Substrates to be treated with Daranà must be made of Cemento 3D or Marmorino Lime with the desired texture.

PREPARATION AND APPLICATION OF THE DARANÀ© METHOD

- ✓ The product is ready to use and does not require dilution.
- 1. Apply a single layer of Decor Fix using a brush, following the texture.
- 2. Spread the Daranà© foil over the still-wet Decor Fix, overlapping the foils by 1 cm, and proceed with this method over the entire surface to be decorated.
- 3. Leave to act for 2 hours (+20°C).
- 4. Remove the Daranà© foil from the surface.
- 5. Leave to dry for 24 hours (+20°C).

IMPORTANT NOTE

- ✓ If you want to make the surface washable, apply a single layer of ProteKto EcoSilan.
- 1. Apply a single layer of ProteKto EcoSilan using a brush.
- 2. Leave the product to rest for approximately 15 minutes (this may vary depending on the ambient temperature and/or (Seasonal)
- 3. Gently wipe the surface with a soft cotton cloth.
- 4. Let dry for 48 hours (+20°C).

TECHNICAL DATA

- ✓ Daranà© coverage: 14 m², variable depending on the texture used.
- ✓ Daranà© size: 21 x 64 ml.
- ✓ Color: Stainless Steel and Gold.
- ✓ Packaging: 1 Daranà© foil 14 m² + 1 Decor Fix 1 L.
- ✓ Do not apply the product at temperatures below +10°C or above +30°C.

WORK REGISTERED WITH

Italian Society of Authors and Publishers (SIAE)
General Management - 00144 Rome - Viale della Letteratura, 30
OLAF SECTION - Published Works Deposit Service

DARANÀ

This is to certify that the work in question has been deposited, accepted pursuant to art. 67, letter b) of the SIAE Regulations and under the conditions established for the provision of the service listed below. The deposit, marked with no. 2022/01949, effective September 27, 2022

OTHER INFORMATION

- ✓ It is recommended to avoid direct contact with highly aggressive substances, such as strongly acidic or basic substances and strongly oxidizing substances (e.g., hair dyes), which can alter the color of the flooring.
- ✓ Vulcanized plastic materials with a high plasticizer content (e.g., tires) may mark the floor if left in prolonged contact with the flooring.
- ✓ The photographic images in the catalog and on the website, as well as the colors shown in the samples, are purely indicative.
- ✓ Use materials from a single production batch for each project.

MAIN CHARACTERISTICS

- ✓ Store in a dry, dry place, away from sunlight.
- ✓ Do not apply on dusty surfaces.
- ✓ Do not apply on wet surfaces.
- ✓ Do not apply on frozen surfaces.
- ✓ Do not apply on still-damp surfaces and repairs.
- ✓ Do not apply in strong sunlight (outdoor application).
- ✓ Do not apply in strong wind (indoor application). (outdoor)
- ✓ Do not apply when it is raining (outdoor application)
- ✓ Make sure the temperature does not drop below +10°C before application
- ✓ Do not apply where rising damp or infiltration moisture has been detected
- ✓ Consult the local weather forecast (outdoor application)
- ✓ Protect windows, doors, etc. well before application

WARNINGS

- ✓ Product for professional use; comply with national standards and regulations.
- ✓ Apply when the surface temperature is above +10°C.
- ✓ Apply to permanently dry surfaces.
- ✓ Protect from direct sunlight and drafts for the first 6 hours.
- ✓ Do not apply to dirty or loose surfaces.
- ✓ Dispose of in accordance with current regulations.
- ✓ Materials exposed to temperature changes (due to transportation, storage, construction site, etc.) may cause substantial changes to the product (e.g., crystallization, partial hardening, fluidification, accelerated or delayed curing).
- ✓ In most cases, restoring the products to optimal conditions will also restore their original condition. Original characteristics
- ✓ Protect surfaces and objects in the installation area from accidental contact.
- ✓ If necessary, request the safety data sheet or contact Nikkolor Italia Technical Customer Service at +39 333 861 8963
- ✓ www.nikkolor.net

DARANÀ

Data collected at +20°C, 65% RH, and no ventilation. They may vary depending on specific construction site conditions: temperature, ventilation, and substrate absorbency.

This information is current as of January 2026 and may be subject to additions and/or changes over time by Nikkolor Italia s.r.l. For any such updates, please consult the website www.nikkolor.net.

Nikkolor Italia s.r.l. is therefore responsible for the validity, timeliness, and currency of its information only if taken directly from its website.

The technical data sheet is prepared based on our best technical and application knowledge. However, as we cannot directly influence construction site conditions and the execution of work, it represents general information that does not bind our company in any way.

A preliminary test is therefore recommended to verify the product's suitability for the intended use.

