

# DECOR FINISH

Issued on 09/15/2015 - Rev. No. 1 of 09/05/2023



## DECOR FINISH

### NANOSTRUCTURED PROTECTIVE VARNISH

TRANSPARENT • WATERPROOF • RESISTANT • DURABLE

Ultra-transparent finish with high performance for continuous surfaces. Protects, seals and enhances floors and wall coverings for indoor and outdoor use, ensuring maximum resistance and long-lasting durability.

- TOTAL PROTECTION**  
Waterproof and dustproof
- HIGH RESISTANCE**  
Resists wear, abrasions and thermal shocks
- EASY TO CLEAN**  
Surfaces always clean with minimal maintenance
- ECO FRIENDLY**  
Formulated with low environmental impact and solvent free

- WATERPROOF**  
Resists water, chlorine and chemical agents
- WEAR-RESISTANT**  
Resists heavy traffic and lift trucks
- ANTI-SLIP**  
Class A (DIN 51097) R11 (DIN 51130)
- EASY TO APPLY**  
2/3 coats with short hair roller

★ ★ ★  
**PROFESSIONAL PERFORMANCE**  
**LONG-LASTING RESULTS**



**1. SHOWER ENCLOSURES**  
Total impermeability against water and steam. Long-lasting protection even in extreme conditions.

**2. CONTINUOUS FLOORS**  
Resistant to foot traffic, wear and abrasions. Perfect for residential and commercial environments.

**3. WALLS AND WALL COVERINGS**  
Protects and enhances decorative surfaces. Ideal for indoor and outdoor use, even in humid areas.

- WATERPROOF**  
Protects against water, humidity and stains
- WEAR-RESISTANT**  
Resists heavy traffic and lift trucks
- RESISTANT TO WEAR**  
High resistance to abrasions and scratches
- RESISTANT TO THERMAL SHOCKS**  
Up to 70°C
- MOLD AND BACTERIA RESISTANT**  
Healthier and safer environments
- EASY TO WASH**  
Simple cleaning, zero complications
- SOLVENT FREE AND LOW VOC**  
Odorless, safe and low environmental impact

#### TECHNICAL DATA

Coverage	8/10 m <sup>2</sup> /L
Application	2/3 coats with short hair roller
Drying time	Walkable in 36 h Use water and furniture after 10 days
Slip resistance	Class A (DIN 51097) - R11 (DIN 51130)
Packaging	2 L; 5 L
Operating temperature	Up to 70°C
Finish	Satin - Matt

# DECOR FINISH

## DESCRIPTION

A latest-generation, single-component, water-based, nanostructured polyacrylic clear coat. It is non-slip, waterproof, and drive-over. Protects and decorates both interior and exterior floors and walls.

## APPLICATIONS

- ✓ Decor Finish is designed for the protection and decoration of floors and walls in 3D Cement, MarmUra, Etna, Terra Veneziana and Microcem-FB.
- ✓ It is used in environments such as shops, warehouses, hospitals, bars, restaurants, mechanical, pharmaceutical, and food industries, private homes, shower stalls, kitchen countertops, furniture, doors, and furnishings.

## SUBSTRATES

- ✓ Floors or shower stalls coated in 3D Cement, MarmUra, Etna, Terra Veneziana and Microcem-FB must be dry and dust-free to avoid compromising the product's perfect adhesion.

## PREPARATION

- ✓ Decor Finish is ready to use; mix thoroughly before use.

## APPLICATION

- ✓ Decor Finish is applied in two or three coats using a short-haired Mohair roller.
- ✓ We do not recommend applying Decor Finish matt directly on white surfaces. The mattifying agent it contains could alter the final appearance of the surface. We recommend applying a first coat of Decor Finish Semi-gloss and then proceed with the application of the matte version.

## FEATURES

- ✓ Excellent surface finish
- ✓ Waterproof and dustproof
- ✓ Easily washable
- ✓ Resistant to abrasion
- ✓ Drive-over
- ✓ Resistant to moderate forklift traffic
- ✓ Consolidating
- ✓ Free from organic solvents
- ✓ Can be applied indoors, odorless
- ✓ Versatile product, adheres to any surface
- ✓ Resists temperature changes
- ✓ Requires minimal maintenance even after years
- ✓ Easy application
- ✓ The product is formulated with a low environmental impact

## OTHER INFORMATION

- ✓ It is recommended to avoid direct contact with highly aggressive substances, such as strongly acidic or basic substances and strongly oxidizing substances (e.g., hair dyes), which can alter the color of the flooring.

# DECOR FINISH

- ✓ Vulcanized plastics with a high plasticizer content (e.g., tires) may leave marks on the floor if left in prolonged contact.
- ✓ The photographic images in the catalog and on the website, as well as the colors shown in the samples, are purely indicative.
- ✓ Use materials from a single production batch for each project.

## MAIN CHARACTERISTICS

- ✓ Store in a dry, dry place, away from sunlight.
- ✓ Do not apply on dusty surfaces.
- ✓ Do not apply on wet surfaces.
- ✓ Do not apply on frozen surfaces.
- ✓ Do not apply on still-damp surfaces and repairs.
- ✓ Do not apply in strong sunlight (outdoor application).
- ✓ Do not apply in strong winds (outdoor application).
- ✓ Do not apply in rain (outdoor application).
- ✓ Make sure the temperature does not drop below +10°C before application.
- ✓ Do not apply where rising or seeping damp has been detected.
- ✓ Check the local weather forecast (outdoor application).
- ✓ Properly cover fixtures, doors, etc. Before application

## WARNINGS

- ✓ Product for professional use; comply with national standards and regulations.
- ✓ Apply when the substrate temperature is above +10°C.
- ✓ Apply to permanently dry substrates.
- ✓ Protect from direct sunlight and drafts for the first 6 hours.
- ✓ Do not apply to dirty or loose surfaces.
- ✓ Dispose of in accordance with current regulations.
- ✓ Materials exposed to temperature changes (due to transport, storage, construction site, etc.) may cause substantial changes to the product (e.g., crystallization, partial hardening, fluidification, accelerated or delayed curing).
- ✓ In most cases, restoring the products to optimal conditions will also restore their original characteristics.
- ✓ Protect surfaces and objects in the application area from accidental contact.
- ✓ If necessary, request the safety data sheet or contact Nikkolor Italia Technical Customer Service at +39 333 861 8963.
- ✓ [www.nikkolor.net](http://www.nikkolor.net)

Data taken at +20°C Temperature, 65% RH, and no ventilation.

They may vary depending on specific construction site conditions: temperature, ventilation, and substrate absorbency.

This information is current as of January 2026 and may be subject to additions and/or changes over time by Nikkolor Italia s.r.l. For any such updates, please consult the website [www.nikkolor.net](http://www.nikkolor.net)

# DECOR FINISH

Nikkolor Italia s.r.l. is therefore responsible for the validity, timeliness, and up-to-dateness of its information only if taken directly from its website.

The technical data sheet is compiled to the best of our technical and application knowledge.

However, since we cannot directly influence site conditions and the execution of work, it represents general information that does not bind our company in any way.

A preliminary test is therefore recommended to verify the product's suitability for the intended use.

