DECOR FINISH UNIKO

Issued on 09/14/2026 - Rev. No. 1 of 09/14/2026





NIKKOLOR®
DECORATIVE PAINTS
ITALIAN DESIGN FOR UNIQUE SURFACES

MORE PROTECTION MORE POSSIBILITIES

Surfaces that stand the test of time, spaces that inspire every day.

DECOR FINISH UNIKO
PROTECTION THAT ENHANCES BEAUTY

- **WATERPROOF** — High resistance to water permeability
- **+40% MORE RESISTANCE** — Higher resistance to foot traffic and abrasion compared to traditional Decor Finish
- **FAST MATURATION** — Complete maturation in 10 days
- **SUITABLE FOR EXTERIORS** — Three-coat system
- **DOES NOT ALTER LIGHT COLORS** — Preserves the original color of decorative surfaces
- **NEUTRAL FINISH** — 8 – 15 Gloss

BATHROOMS AND WET AREAS — Protection from water and humidity

FLOORS — Resistant to foot traffic and abrasion

WALLS AND COATINGS — Enhances decorative surfaces

18 m² with 2.5 L in two coats	139 mL/m² theoretical consumption in two coats	2 | 3 number of coats interior | exterior	10 days complete maturation (vs. 20 days with traditional Decor Finish)	8 – 15 Gloss brightness	LOW ENVIRONMENTAL IMPACT Solvent-free

NIKKOLOR® ITALY

MATERIAL | PROTEZTION | DESIGN | DURABILITY

www.nikkolor.net

MADE IN ITALY

DECOR FINISH UNIKO

DESCRIPTION
Decor Finish Uniko is a single-component, water-based, nanostructured polyacrylic transparent protective finish, developed to provide high-performance protection and resistance.

Characterized by excellent resistance to water permeability, foot traffic, and abrasion, it protects and enhances floors, walls, and decorative coatings—both indoors and outdoors—while preserving the original appearance and color tone of the treated surfaces.

FIELDS OF APPLICATION
- ✓ Decor Finish Uniko is designed for the protection and finishing of floors, walls, and decorative coatings created with Cemento 3D, MarmUra, Etna, Terra Veneziana, and Microcem-FB.
- ✓ Due to its high-performance properties, it is suitable for surfaces in residential, commercial, and professional settings, including private homes, shops, bars, restaurants, offices, hospitality facilities, hospitals, warehouses, and industrial environments.
- ✓ It is also suitable for protecting shower enclosures, kitchen countertops, furniture, doors, and decorative furnishings—both indoors and outdoors—provided the specified application procedure is followed.

PREPARATION
- ✓ Decor Finish Uniko must be diluted before use; DO NOT apply the product undiluted.
- ✓ Add 850 g/ml of potable water directly into the container.
- ✓ Close the lid securely and shake vigorously for one minute.
- ✓ Allow the mixture to rest for 1–2 minutes; the product is then ready for application.

APPLICATION
- ✓ Decor Finish Uniko should be applied using a short-nap mohair roller.
- ✓ 2 coats: for walls and surfaces not subject to direct contact with water.
- ✓ 3 coats: for walls and surfaces subject to direct contact with water—such as shower enclosures, bathtubs, and similar areas—as well as for all types of flooring. Decor Finish Uniko provides significant protective properties from the very first coat, with performance progressively increasing as the full application cycle is completed and the product cures.

FEATURES AND BENEFITS
- ✓ Excellent surface finish.
- ✓ Can be tinted.
- ✓ Highly resistant to water permeability; acts as a dust-proofing agent.
- ✓ Easy to clean and maintain.
- ✓ Highly resistant to abrasion and foot traffic.
- ✓ Suitable for vehicular traffic.
- ✓ Resistant to moderate forklift traffic.
- ✓ Consolidates the treated surface.
- ✓ Free from organic solvents.
- ✓ Odorless; suitable for indoor application.
- ✓ Highly versatile, with excellent adhesion to a wide range of substrates.
- ✓ Resistant to thermal shock.
- ✓ Requires minimal long-term maintenance.
- ✓ Easy to apply.

DECOR FINISH UNIKO

- ✓ Formulated for low environmental impact.
- ✓ Effective protection from the very first coat.
- ✓ Over 40% greater resistance to foot traffic compared to traditional Decor Finish.
- ✓ Reaches full cure in 10 days, compared to approximately 20 days for traditional Decor Finish.
- ✓ Reduced color shift in light shades.
- ✓ Neutral finish—neither strictly matte nor semi-gloss—with a sheen level typically between 8 and 15 Gloss, varying based on the surface and the number of coats applied.
- ✓ Suitable for interior and exterior use; requires a 2-coat system for interiors and a 3-coat system for exteriors.
- ✓ Safety information: Please refer to the latest Safety Data Sheet (SDS) for hazard classification, precautions for use, and personal protective equipment (PPE) requirements.

COVERAGE AND CONSUMPTION

- ✓ The approximate coverage of Decor Finish Uniko is 18 m^2 per 2.5 L container, which corresponds to about 7.2 m^2/L for a complete two-coat system.
- ✓ The total theoretical consumption is approximately 139 ml/m^2 for a two-coat system.
- ✓ Actual coverage may vary depending on the substrate's absorption, porosity, and roughness, as well as the amount of product applied and the application method.

TECHNICAL DATA

- ✓ Appearance: Liquid
- ✓ Color: Milky
- ✓ pH: > 9
- ✓ Concentrated product: 1.642 L (approx. 1.685 kg)
- ✓ Specific gravity of concentrate: 1.026 ± 0.05 kg/L
- ✓ Water to be added: 850 g/ml
- ✓ Nominal final volume: approx. 2.5 L
- ✓ Effective dilution: approx. 50.4% by weight relative to the concentrate
- ✓ Store in original, tightly sealed packaging in a dry place at temperatures between +5°C and +30°C.
- ✓ The product is not classified as hazardous under EC Regulation 1272/2008 (CLP).
- ✓ Safety information: Refer to the latest Safety Data Sheet (SDS) for hazard classification, precautions for use, and personal protective equipment (PPE).

APPLICATION CONDITIONS AND LIMITATIONS

- ✓ Store the product in a dry environment, protected from moisture and direct sunlight.
- ✓ Do not apply to dusty, dirty, or improperly prepared surfaces.
- ✓ Do not apply to wet surfaces or surfaces with standing water.
- ✓ Do not apply to frozen surfaces or surfaces at risk of freezing.
- ✓ Do not apply to substrates, skim coats, or repaired areas that are not completely dry or still contain residual moisture.
- ✓ Do not apply in cases of rising damp (capillary moisture) or water infiltration.
- ✓ Before application, ensure that both the substrate and ambient temperatures are at least +10°C.
- ✓ For exterior applications, avoid working in direct, intense sunlight, strong wind, rain, or other adverse weather conditions. For outdoor applications, check the weather forecast for the time of application and the hours that follow, in order to avoid rain, frost, or any conditions that could compromise the proper drying of the product.

DECOR FINISH UNIKO

- ✓ Before application, carefully protect fixtures, doors, glass, metal elements, and any other surfaces that are not to be treated.
- ✓ Ensure that the substrate is stable, cohesive, clean, dry, and properly prepared before proceeding with the application.

WARNINGS

- ✓ This product is intended for professional use. Use in compliance with all applicable national regulations and provisions.
- ✓ During application and for at least the following 6 hours, protect the surface from direct sunlight, drafts, and any environmental conditions that could compromise the proper drying of the product.
- ✓ Dispose of the product, any residues, and packaging in accordance with current regulations.
- ✓ Exposing the product to significant temperature fluctuations during transport, storage, or while on the job site may cause temporary changes to its physical properties, such as crystallization, partial hardening, or variations in viscosity and drying times.
- ✓ If the product has been exposed to temperatures outside the specified storage range, gradually bring it back to the recommended ambient conditions and thoroughly check its homogeneity, consistency, and integrity before use. → If any persistent alterations to the product are observed, do not proceed with the application; instead, contact the Nikkolor Italia Technical Customer Service.
- ✓ Before application, take care to protect surfaces, structures, fixtures, glass, and any other elements in the work area that are not to be treated, ensuring they do not come into accidental contact with the product.
- ✓ Consult the Safety Data Sheet (SDS) before use and follow the instructions provided therein. For further technical information, please contact the Nikkolor Italia Technical Customer Service at +39 333 861 8963.
- ✓ Official website: www.nikkolor.net

Data measured at a temperature of +20°C, 65% relative humidity, and in the absence of ventilation. Values may vary depending on specific site conditions, such as temperature, ventilation, and the absorbency of the substrate.

This information may be subject to additions and/or changes over time by Nikkolor Italia S.r.l. Please check the website www.nikkolor.net for any updates.

Nikkolor Italia S.r.l. is responsible for the validity, accuracy, and currency of its information only when such information is obtained directly from its official website.

This technical data sheet has been prepared based on our best technical and application-related knowledge.

However, as we cannot directly control conditions on-site or the execution of the work, the information provided serves only as a general guide and is not binding upon Nikkolor Italia S.r.l. in any way.

We therefore recommend conducting a preliminary test to verify the suitability of the product for its intended use.

DECOR FINISH UNIKO







Nikkolor Italia s.r.l.
V.le Vittorio Veneto, 186 - 96014 Floridia (SR)
+39 0931 941789 - www.nikkolor.net